

# Cabinet Fittings & Accessories

## Moulded Press-Fit Reflex Ports (Open-ended)

An attractive range of mouldings for use in reflex loaded loudspeaker cabinets.

Speedy assembly is achieved by simply pressing the slightly tapered tubes into a correctly dimensioned circular hole. Short external splines moulded on the tube just behind the thin front flange bite into and permanently grip the cabinet wall or baffle, be it chipboard, medium density fibreboard or other similar material.

A smoothly rounded mouth transition to the flange helps avoid 'chuffing' in high power units with an extended bass response which move large amounts of air (except 6751). The rear of the flange is moulded flat, unless indicated 'flange relief' - a groove which allows space for burrs around the edge of the mounting hole and to improve the seating of the outer edge of the flange.

The following list is representative of the items available. If your requirements are not met by any of these, please let us know your exact specifications.

Type Number	D (mm)	L (mm)	t (mm)	Rounded Mouth	F (mm)	f (mm)	Flange Relief	No. of Splines
CL-T 3580	34.5 - 35.0	77	2.5	Yes	44.0	2.5	No	8
CL-T57125	55.0 - 56.0	124	2.5	Yes	73.5	4.0	Yes	8
CL-T 6751	65.0 - 66.0	50.8	2.5	No	84.9	4.0	Yes	8
CL-T 7090 *	69.0 - 70.5	91.5	3.0	Yes	83.0	6.0	No	8

**Standard colour: Black**



For clarity, the tube taper is not shown in the drawing

